



**TNR INDUSTRIAL DOORS INC.**

**SHOP DRAWING, CHILLFAST MODEL, LEFT HAND**

EXT. DETAIL: FREEZER DOOR - DIRECT DRIVE OPERATOR

LIMITATIONS: (OW<=12' 0" & OH<=16' 0")

DATE DR'N: MAR. 26, 2014 REVISION: REL

DRAWN BY: R.B. DRAWING No.: D-600-0099

ELECTRICAL CRITERIA: FREQUENCY INVERTER DRIVE

CONTROL PANEL NEMA/EEMAC 4 STD. OR \_\_\_\_\_

PRIMARY POWER SUPPLY: \_\_\_\_\_ Volts, 3 Phase, 60 Hertz

OPERATOR CRITERIA: DIRECT DRIVE

OPERATOR NEMA/EEMAC 4 STD. OR \_\_\_\_\_

0.85 HP, DOOR SPEED: OPEN UP TO \_\_\_\_\_ ips, CLOSE UP TO \_\_\_\_\_ ips

END USER:

DEALER:

DOOR SIZE: SERIAL No.: TNR-

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - STAINLESS DOOR HOOD	<input type="checkbox"/> - LOOP DETECTOR	- SPEEDS UP TO 75 IPS OPEN, 30 IPS CLOSE
<input type="checkbox"/> - HAND CRANK EXTENSION ____ FT	<input type="checkbox"/> - WIRELESS RECEIVER	- NEMA 4 CONTROL PANEL & OPERATOR
<input type="checkbox"/> - CURTAIN COLOUR _____	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- FREQUENCY DRIVE PANEL
<input type="checkbox"/> - CURTAIN PRESSURE RIBS	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. _____	- PROGRAMMABLE CONTROLLER DIGITAL LIMITS
<input type="checkbox"/> -	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- NON FUSED ROTARY DISCONNECT
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- TIMER TO CLOSE (USER SELECT)
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- OPTICAL REVERSING EDGE
<input type="checkbox"/> -	<input type="checkbox"/> - FREQUENCY INVERTER **	- THRU-BEAM PHOTOSWITCH
<input type="checkbox"/> -	<input type="checkbox"/> ** TRANSFORMER PANEL(13"X13"X5") REQ'D IF VOLTAGE IS NOT 230V	- 3" HIGH, YELLOW PVC LOOP
<input type="checkbox"/> -		- WHITE ALUMINUM DOOR HOOD
<input type="checkbox"/> -		- BLUE PVC INSULATED CURTAIN 10mm THK
<input type="checkbox"/> -		-