



TNR INDUSTRIAL DOORS INC.

SHOP DRAWING, MODEL HSR-007, LEFT HAND

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES	EXT. DETAIL: DIRECT DRIVE OPERATOR
<input type="checkbox"/> - STORM HOOKS	<input type="checkbox"/> - LOOP DETECTOR	- SPEEDS UP TO 70 IPS OPEN, 28 IPS CLOSE	LIMITATIONS: (OW<=19' 0" & OH<=19' 0")
<input type="checkbox"/> - WINDOW PANEL FROM ____ TO ____	<input type="checkbox"/> - WIRELESS RECEIVER	- TIMER TO CLOSE (USER SELECT)	DATE DR'N: MAR. 19, 2014
<input type="checkbox"/> - STAINLESS STEEL SLATS	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. ____	- NEMA 4 CONTROL PANEL & OPERATOR	REVISION: RELEASE
<input type="checkbox"/> - SLATS PAINTED RAL ____	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY. ____	- PROGRAMMABLE CONTROLLER	DRAWN BY: R.B.
<input type="checkbox"/> -	<input type="checkbox"/> - MOTION DETECTOR, QTY. ____	- FREQUENCY INVERTER	DRAWING No.: D-600-0102
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. ____	- OPTICAL REVERSING EDGE	ELECTRICAL CRITERIA: FREQUENCY INVERTER DRIVE
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. ____	- THRU-BEAM PHOTOEYE	CONTROL PANEL NEMA/EEMAC 4 STD. OR ____
<input type="checkbox"/> -	<input type="checkbox"/> -	-	PRIMARY POWER SUPPLY: ____ Volts, 3 Phase, 60 Hertz
<input type="checkbox"/> -	<input type="checkbox"/> -	-	OPERATOR CRITERIA: DIRECT DRIVE
<input type="checkbox"/> -	<input type="checkbox"/> -	-	OPERATOR NEMA/EEMAC 4 STD. OR ____
<input type="checkbox"/> -	<input type="checkbox"/> -	-	____ HP, DOOR SPEED: OPEN UP TO @ ____ ips, CLOSE UP TO @ ____ ips
<input type="checkbox"/> -	<input type="checkbox"/> -	-	END USER:
<input type="checkbox"/> -	<input type="checkbox"/> -	-	DEALER:
<input type="checkbox"/> -	<input type="checkbox"/> -	-	DOOR SIZE:
			SERIAL No.: TNR-